

Unit: mm (in)

FRONT WHEEL/SUSPENSION/STEERING

ITEM		STANDARD	SERVICE LIMIT
Minimum tire tread depth		—	To the indicator
Cold tire pressure	Driver only	200 kPa (2.00 kgf/cm ² , 29 psi)	—
	Driver and passenger	200 kPa (2.00 kgf/cm ² , 29 psi)	—
Axle runout		—	0.20 (0.008)
Wheel rim runout	Radial	—	2.0 (0.08)
	Axial	—	2.0 (0.08)
Wheel balancer weight		—	60 g (2.1 oz) max.
Fork	Spring free length	412.4 (16.24)	404.1 (15.91)
	Spring direction	With the tightly wound end facing down	—
	Pipe runout	—	0.20 (0.008)
	Recommended fork fluid	Honda Ultra Cushion Oil No.10	—
	Fluid level	131 (5.2)	—
Fluid capacity		206 ± 2.5 cm ³ (7.0 ± 0.08 US oz, 7.3 ± 0.09 Imp oz)	—

Unit: mm (in)

REAR WHEEL/SUSPENSION

ITEM		STANDARD	SERVICE LIMIT
Minimum tire tread depth		—	To the indicator
Cold tire pressure	Driver only	200 kPa (2.00 kgf/cm ² , 29 psi)	—
	Driver and passenger	225 kPa (2.25 kgf/cm ² , 33 psi)	—
Axle runout		—	0.20 (0.008)
Wheel rim runout	Radial	—	2.0 (0.08)
	Axial	—	2.0 (0.08)
Wheel balancer weight		—	60 g (2.1 oz) max.
Drive chain	Size/link	DID428VI3-124LE	—
	Slack	25 – 35 (1.0 – 1.4)	—