

Specifications

■ Service Data

Tyre size	Front	120/70ZR17M/C (58W)
	Rear	160/60ZR17M/C (69W)
Tyre type	Radial, tubeless	
Recommended Tyres	Front	BRIDGESTONE BT023F G METZELER ROADTEC Z8 INTERACT E
	Rear	BRIDGESTONE BT023R G METZELER ROADTEC Z8 INTERACT
Tyre air pressure	Front	250 kPa (2.50 kgf/cm ² , 36 psi)
	Rear	290 kPa (2.90 kgf/cm ² , 42 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plugs	(standard) IFR6G-11K (NGK)	
Spark plug gap	(non-adjustable) 1.00 to 1.10 mm (0.039 to 0.043 in)	
Idle speed	1,200 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving," SAE 10W-30, JASO T 903 standard MA	

NC700S/SA

After draining 3.1 litres (3.3 US qt,
2.7 Imp qt)

After draining & engine oil filter change 3.4 litres (3.6 US qt,
3.0 Imp qt)

After disassembly 3.7 litres (3.9 US qt,
3.3 Imp qt)

NC700SD

After draining 3.2 litres (3.4 US qt,
2.8 Imp qt)

After draining & engine oil filter change 3.4 litres (3.6 US qt,
3.0 Imp qt)

After draining, engine & clutch oil filter change 3.4 litres (3.6 US qt,
3.0 Imp qt)

After disassembly 4.1 litres (4.3 US qt,
3.6 Imp qt)

Recommended brake fluid Honda DOT 4 Brake Fluid

Cooling system capacity 1.69 litres (1.79 US qt, 1.49 Imp qt)

Recommended coolant Pro Honda HP Coolant