

■ **Service Data**

| | | |
|---------------------|-------------------------------|---|
| Tire size | Front | 120/70ZR17M/C (58W) |
| | Rear | 190/55ZR17M/C (75W) |
| Tire type | Radial, tubeless | |
| Recommended Tire | Front | BRIDGESTONE BATTLEAX HYPERSPORT S21F M |
| | | DUNLOP SPORTMAX D214F G |
| | Rear | BRIDGESTONE BATTLEAX HYPERSPORT S21R M |
| | | DUNLOP SPORTMAX D214 G |
| Tire air pressure | Front | 36 psi (250 kPa, 2.50 kgf/cm ²) |
| | Rear | 42 psi (290 kPa, 2.90 kgf/cm ²) |
| Minimum tread depth | Front | 0.06 in (1.5 mm) |
| | Rear | 0.08 in (2.0 mm) |
| Spark plug | (standard) | IMR9E-9HES (NGK) or VUH27ES (DENSO) |
| Spark plug gap | 0.03 - 0.04 in (0.8 - 0.9 mm) | |
| Idle speed | 1,200 ± 100 rpm | |

| | | |
|-----------------------------------|---|-------------------|
| Recommended engine oil | API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil | |
| | After draining | 2.9 US qt (2.7 L) |
| Engine oil capacity | After draining & engine oil filter change | 3.2 US qt (3.0 L) |
| | After disassembly | 3.8 US qt (3.6 L) |
| Recommended brake fluid | Honda DOT 4 Brake Fluid | |
| Cooling system capacity | 2.91 US qt (2.75 L) | |
| Recommended coolant | Pro Honda HP Coolant | |
| Recommended drive chain lubricant | Pro Honda HP Chain Lube or equivalent lubricant | |
| Drive chain slack | 1 9/16 - 1 15/16 in (40 - 50 mm) | |
| Standard drive chain | RK525ROZ7 | |
| | No. of links | 116 |
| Standard sprocket size | Drive sprocket | 15T |
| | Driven sprocket | 44T |