

Specifications

| | | |
|-----------------------------------|---------------------------------------|-----|
| Recommended drive chain lubricant | Pro Honda HP Chain Lube or equivalent | |
| Drive chain slack | 1 3/8 to 1 3/4 in (35 to 45 mm) | |
| Standard drive chain | DID 525HV3 | |
| | No. of links | 124 |
| Standard sprocket sizes | Drive sprocket | 16T |
| | Driven sprocket | 42T |

■ Bulbs

| | |
|--------------------------|---------------|
| Headlight | LED |
| Brake/Tail light | LED |
| Front turn signal lights | 12V-21/5W × 2 |
| Rear turn signal lights | 12V-21W × 2 |
| License plate light | 12V-5W |

■ Fuses

| | |
|-------------|--------------------------|
| Main fuse | 30A |
| Other fuses | 30A, 20A, 15A, 10A, 7.5A |

■ Torque Specifications

| | |
|--|---------------------------------|
| Skid plate bolts | 19 lbf-ft (26 N·m, 2.7 kgf·m) |
| Bolts B | 6.6 lbf-ft (9.0 N·m, 0.9 kgf·m) |
| Bolts A | 6.6 lbf-ft (9.0 N·m, 0.9 kgf·m) |
| Oil filter | 19 lbf-ft (26 N·m, 2.7 kgf·m) |
| Engine oil drain bolts | 22 lbf-ft (30 N·m, 3.1 kgf·m) |
| Clutch oil filter cover bolts | 9 lbf-ft (12 N·m, 1.2 kgf·m) |
| Rear wheel axle nut | 74 lbf-ft (100 N·m, 10.2 kgf·m) |
| Drive chain adjusting lock nuts | 20 lbf-ft (27 N·m, 2.8 kgf·m) |
| Front wheel axle nut | 44 lbf-ft (60 N·m, 6.1 kgf·m) |
| Front wheel axle pinch bolts | 16 lbf-ft (22 N·m, 2.2 kgf·m) |
| Front wheel brake caliper mounting bolts | 33 lbf-ft (45 N·m, 4.6 kgf·m) |