

Specifications

	DID 520V0 or RK 520KHO	
Standard drive chain	NC750X/XA	
	No. of links	114
	NC750XD	
	No. of links	112
	Drive sprocket	17T
Standard sprocket size	NC750X/XA	
	Driven sprocket	43T
	NC750XD	
	Driven sprocket	39T

■ Bulbs

Headlight	LED
Brake light/Taillight	LED
Front turn signal light	12 V-21/5 W x 2
Rear turn signal light	12 V-21 W x 2
Position light	LED
License plate light	12 V-5 W

■ Fuses

Main fuse		30 A
Other fuse	NC750X	15 A, 7.5 A
	NC750XA/XD	30 A, 15 A, 7.5 A

■ Torque Specifications

Maintenance lid screw	2.2 lbf-ft (3 N·m, 0.3 kgf·m)
Oil filter	19 lbf-ft (26 N·m, 2.7 kgf·m)
Engine oil drain bolt	22 lbf-ft (30 N·m, 3.1 kgf·m)
Rear wheel axle nut	72 lbf-ft (98 N·m, 10.0 kgf·m)
Drive chain adjusting lock nut	15 lbf-ft (21 N·m, 2.1 kgf·m)
Front wheel axle shaft	55 lbf-ft (74 N·m, 7.5 kgf·m)
Front wheel brake caliper mounting bolt	22 lbf-ft (30 N·m, 3.1 kgf·m)
Front wheel axle pinch bolt	16 lbf-ft (22 N·m, 2.2 kgf·m)
NC750XD	
Parking brake caliper mounting bolt	23 lbf-ft (31 N·m, 3.2 kgf·m)