

GENERAL INFORMATION

HYDRAULIC BRAKE:

ITEM	Q'TY	THREAD DIA. (mm)	TORQUE N·m (kgf·m, lbf·ft)	REMARKS
Brake hose oil bolt	5	10	34 (3.5, 25)	
Rear brake caliper pad pin	1	10	18 (1.8, 13)	
Rear caliper bleed valve	1	8	5.9 (0.6, 4.3)	
Rear brake caliper slide pin bolt	1	12	27 (2.8, 20)	
Rear brake caliper mounting bolt	1	8	23 (2.3, 17)	
Rear brake hose clamp bolt	1	5	3.9 (0.4, 2.9)	
Rear master cylinder push rod joint nut	1	8	18 (1.8, 13)	
Rear brake reservoir hose joint screw	1	4	1.5 (0.15, 1.1)	NOTE 2
Rear master cylinder reservoir cap screw	2	4	1.5 (0.15, 1.1)	
Rear master cylinder reservoir mounting bolt	1	6	12 (1.2, 9)	
Rear master cylinder mounting bolt	2	6	9.8 (1.0, 7)	
Brake pedal pivot bolt	1	8	18 (1.8, 13)	
Front brake caliper mounting bolt	4	10	45 (4.6, 33)	NOTE 6
Front brake caliper assembly bolt	8	8	23 (2.3, 17)	NOTE 2
Front brake caliper pad pin	2	10	16 (1.6, 12)	
Front caliper bleed valve	2	8	7.8 (0.8, 5.8)	
Front brake hose clamp	1	6	8.8 (0.9, 6.5)	
Front brake hose 3-way joint bolt	1	6	9.8 (1.0, 7)	
Front brake hose clamp (left side)	1	6	9.8 (1.0, 7)	
Front master cylinder reservoir cap screw	2	4	1.5 (0.15, 1.1)	
Front master cylinder reservoir stay bolt	1	6	12 (1.2, 9)	
Front brake light switch screw	1	4	1.0 (0.1, 0.7)	
Front master cylinder reservoir mounting nut	1	6	5.9 (0.6, 4.3)	NOTE 5
Front brake lever pivot bolt	1	6	1.0 (0.1, 0.7)	
Front brake lever pivot nut	1	6	5.9 (0.6, 4.3)	
Front master cylinder bleed valve	1	8	5.9 (0.6, 4.3)	
Front master cylinder holder bolt	2	6	12 (1.2, 9)	

LIGHTS/METERS/SWITCHES:

ITEM	Q'TY	THREAD DIA. (mm)	TORQUE N·m (kgf·m, lbf·ft)	REMARKS
Ignition switch mounting one-way bolt	2	8	26 (2.7, 20)	
Right handlebar switch screw	2	4	0.9 (0.09, 0.7)	
Combination meter assembly screw	3	5	1.0 (0.1, 0.7)	
Side stand switch special bolt	1	6	9.8 (1.0, 7)	NOTE 6

OTHERS:

ITEM	Q'TY	THREAD DIA. (mm)	TORQUE N·m (kgf·m, lbf·ft)	REMARKS
Side stand socket bolt	2	10	54 (5.5, 40)	
Side stand pivot bolt	1	10	9.8 (1.0, 7)	
Side stand pivot nut	1	10	29 (3.0, 22)	