

MAINTENANCE SCHEDULE

Perform the Pre-ride inspection in the Owner's Manual at each scheduled maintenance period.

I: Inspect and Clean, Adjust, Lubricate or Replace if necessary. C: Clean. R: Replace. A: Adjust. L: Lubricate.

The following items require some mechanical knowledge: Certain items (particularly those marked * and **) may require more technical information and tools. Consult their authorized HONDA dealer.

ITEMS	FREQUENCY	WHICHEV- ER COMES FIRST ↓	⇨ ODOMETER READING (NOTE 1)								REFER TO PAGE
			× 1,000 km	1	6	12	18	24	30	36	
			× 1,000 mi	0.6	4	8	12	16	20	24	
Months		6	12	18	24	30	36				
* FUEL LINE					I		I		I	3-4	
* THROTTLE OPERATION					I		I		I	3-5	
* AIR CLEANER		NOTE 2					R		R	3-6	
SPARK PLUG									EVERY 12,000 km (7,200 mi) I EVERY 24,000 mi (14,400 km) R	3-7	
* VALVE CLEARANCE					I		I		I	3-11	
ENGINE OIL					R		R		R	3-15	
ENGINE OIL FILTER					R		R		R	3-15	
* ENGINE IDLE SPEED					I	I	I	I	I	3-18	
RADIATOR COOLANT		NOTE 3					I		R	3-18	
* COOLING SYSTEM							I		I	3-19	
* SECONDARY AIR SUPPLY SYSTEM							I		I	3-19	
DRIVE CHAIN									EVERY 800 km (500 mi) I, L	3-20	
DRIVE CHAIN SLIDER							I		I	3-24	
BRAKE FLUID		NOTE 3					I	I	R	3-25	
BRAKE PAD WEAR							I	I	I	3-25	
BRAKE SYSTEM							I		I	3-26	
* BRAKE LIGHT SWITCH							I		I	3-27	
* HEADLIGHT AIM							I		I	3-28	
CLUTCH SYSTEM							I		I	3-28	
CLUTCH FLUID		NOTE 3					I	I	R	3-28	
SIDE STAND							I		I	3-29	
* SUSPENSION							I		I	3-29	
* NUTS, BOLTS, FASTENERS							I		I	3-31	
** WHEELS/TIRES							I		I	3-31	
** STEERING HEAD BEARINGS							I		I	3-31	

* Should be serviced by an authorized HONDA dealer, unless the owner has proper tools and service data and is mechanically qualified.

** In the interest of safety, we recommend these items be serviced only by an authorized HONDA dealer.

- NOTES:
1. At higher odometer reading, repeat at the frequency interval established here.
 2. Service more frequently if the motorcycle is ridden in unusually wet or dusty areas.
 3. Replace every 2 years, or at indicated odometer interval, whichever comes first. Replacement requires mechanical skill.