

# 4. LUBRICATION SYSTEM

LUBRICATION SYSTEM DIAGRAM	4-0	OIL STARAINER/PRESSURE RELIEF VALVE	4-4
SERVICE INFORMATION	4-1	OIL PUMP	4-8
TROUBLESHOOTING	4-2	OIL COOLER	4-13
OIL PRESSURE INSPECTION	4-3		

## SERVICE INFORMATION

### GENERAL

#### ▲WARNING

- When the engine must be running to do some work, make sure the area is well-ventilated. Never run the engine in an enclosed area. The exhaust contains poisonous carbon monoxide gas that may cause loss of consciousness and lead to death. Run the engine in an open area or with an exhaust evacuation system in an enclosed area.
- Used engine oil may cause skin cancer if repeatedly left in contact with the skin for prolonged periods. Although this is unlikely unless you handle used oil on a daily basis, it is still advisable to thoroughly wash your hands with soap and water as soon as possible after handling used oil. **KEEP OUT OF REACH OF CHILDREN.**

- The oil pump can be serviced with the engine installed in the frame.
- The service procedures in this section must be performed with the engine oil drained.
- When removing and installing the oil pump, use care not to allow dust or dirt to enter the engine.
- If any portion of the oil pump is worn beyond the specified service limits, replace the oil pump as an assembly.
- After the oil pump has been installed, check that there are no oil leaks and that oil pressure is correct.

### SPECIFICATIONS

Unit: mm (in)

ITEM		STANDARD	SERVICE LIMIT	
Engine oil capacity	At draining	3.8 ℓ (4.0 US qt, 3.3 Imp qt)	————	
	At disassembly	4.6 ℓ (4.9 US qt, 4.0 Imp qt)	————	
	At oil filter change	3.9 ℓ (4.1 US qt, 3.4 Imp qt)	————	
Recommended engine oil		HONDA 4-stroke oil or equivalent motor oil API service classification SE, SF or SG Viscosity: SAE 10W-40	————	
Oil pressure at oil pressure switch		490 kPa (5.0 kgf/cm <sup>2</sup> , 71 psi) at 5,400 min <sup>-1</sup> (rpm)/(80 °C/176 °F)	————	
Oil pump rotor	Feed pump	Tip clearance	0.15 (0.006) max.	0.20 (0.008)
		Body clearance	0.15-0.21 (0.006-0.008)	0.35 (0.014)
		Side clearance	0.04-0.09 (0.002-0.004)	0.12 (0.005)
	Cooler pump	Tip clearance	0.15 (0.006) max.	0.20 (0.008)
		Body clearance	0.15-0.21 (0.006-0.008)	0.35 (0.014)
		Side clearance	0.04-0.09 (0.002-0.004)	0.12 (0.005)