

GENERAL INFORMATION

Unit: mm (in)

FRONT WHEEL/SUSPENSION/STEERING		STANDARD	SERVICE LIMIT
ITEM			
Minimum tire tread depth			1.5 (0.06)
Cold tire pressure	Up to 90 kg (200 lb) load	290 kPa (2.90 kgf/cm ² , 42 psi)	
	Up to maximum weight capacity	290 kPa (2.90 kgf/cm ² , 42 psi)	
Axle runout			0.20 (0.008)
Wheel rim runout	Radial		2.0 (0.08)
	Axial		2.0 (0.08)
Fork	Spring free length	232.9 (9.17)	228.2 (8.98)
	Spring direction	With the tapered end facing down	
	Pipe runout		0.20 (0.008)
	Recommended fork fluid	Pro Honda Suspension Fluid SS-8	
	Fluid level	142 (5.6)	
	Fluid capacity	483 ± 2.5 cm ³ (16.3 ± 0.08 US oz, 17.1 ± 0.09 Imp oz)	
Steering head bearing pre-load		10 - 15N (1.0 - 1.5 kgf)	

Unit: mm (in)

REAR WHEEL/SUSPENSION			STANDARD	SERVICE LIMIT
ITEM				
Minimum tire tread depth				2.0 (0.08)
Cold tire pressure	Up to 90 kg (200 lb) load		290 kPa (2.90 kgf/cm ² , 42 psi)	
	Up to maximum weight capacity		290 kPa (2.90 kgf/cm ² , 42 psi)	
Axle runout				0.20 (0.008)
Wheel rim runout	Radial			2.0 (0.08)
	Axial			2.0 (0.08)
Drive chain	Size/link	DID	DID50ZVS-110LE	
		RK	RK50LFOZ1-110LE	
	Slack		25 - 35 (1.0 - 1.4)	50 (2.0)
Shock absorber	Spring installed length		209.1 (8.23)	