


# GENERAL INFORMATION

## FRAME

ITEM	Q'TY	THREAD DIA. (mm)	TORQUE N-m (kgf-m, lbf-ft)	REMARKS	
<b>FRAME BODY PANELS/EXHAUST SYSTEM:</b>					
Side stand pivot bolt	1	10	10 (1.0, 7)	NOTE 8	
Side stand pivot lock nut	1	10	29 (3.0, 22)		
Main stand mounting bolt	1	10	54 (5.5, 40)		
Main footpeg holder socket bolt	4	8	26 (2.7, 20)		
Passenger footpeg holder bolt	4	8	26 (2.7, 20)		
Bank sensor	2	8	22 (2.2, 16)		
Exhaust pipe joint nut	8	7	20 (2.0, 14)		
Muffler band bolt	4	8	17 (1.7, 12)		
Muffler bracket bolt	2	8	26 (2.7, 20)		
Seat rail mounting bolt	4	10	44 (4.5, 33)		
<b>FUEL SYSTEM (Programmed Fuel Injection):</b>					
Fuel tube sealing nut (throttle body side)	1	12	22 (2.2, 16)		
Fuel tube banjo bolt (fuel tank side)	1	12	22 (2.2, 16)		
Service check bolt	1	6	15 (1.5, 11)		
Fuel pump mounting nut	6	6	12 (1.2, 9)		
					
Fuel filler cap bolt	3	4	2 (0.2, 1.4)		
<b>ENGINE MOUNTING:</b>					
Side stand bracket bolt	2	10	54 (5.5, 40)		
Engine hanger nut (rear/upper)	1	12	64 (6.5, 47)		
Engine hanger nut (rear/lower)	1	12	64 (6.5, 47)		
Engine hanger bolt	3	10	40 (4.1, 30)		
Engine hanger adjusting bolt	2	22	11 (1.1, 8)		
Engine hanger adjusting bolt lock nut	2	22	54 (5.5, 40)		
<b>CLUTCH/GEARSHIFT LINKAGE:</b>					
Clutch master cylinder holder bolt	2	6	12 (1.2, 9)		
Clutch master cylinder cap screw	2	4	1 (0.15, 1.1)		
Clutch lever pivot bolt	1	6	1 (0.1, 0.7)		
Clutch lever pivot nut	1	6	6 (0.6, 4.3)		
Clutch lever adjuster	1	5	4 (0.4, 2.9)		
Clutch switch screw	1	4	1 (0.12, 0.9)		
Gearshift pedal bolt	1	6	10 (1.0, 7)		
<b>FRONT WHEEL/SUSPENSION/STEERING:</b>					
Handlebar pinch bolt	2	8	26 (2.7, 20)	NOTE 8 See page 13-34	
Handlebar weight mounting screw	2	6	10 (1.0, 7)		
Steering stem nut	1	24	103 (10.5, 76)		
Top thread A	1	26	25 (2.5, 18)		
Top thread B	1	26			
Fork top bridge pinch bolt	2	8	23 (2.3, 17)	NOTE 8 NOTE 2	
Fork bottom bridge pinch bolt	2	10	49 (5.0, 36)		
Front axle bolt	1	14	59 (6.0, 43)		
Front axle holder bolt	4	8	22 (2.2, 16)		
Front brake disc mounting bolt	12	6	20 (2.0, 14)		
Fork cap	2	37	23 (2.3, 17)		
Fork socket bolt	2	8	20 (2.0, 14)		
Fork damper lock nut	2	10	20 (2.0, 14)		