

MAINTENANCE SCHEDULE

'99:

Perform the Pre-ride inspection in the Owner's Manual at each scheduled maintenance period.

I: Inspect and Clean, Adjust, Lubricate or Replace if necessary. C: Clean. R: Replace. A: Adjust. L: Lubricate.

The following items require some mechanical knowledge. Certain items (particularly those marked * and **) may require more technical information and tools. Consult their authorized HONDA dealer.

ITEMS	FREQUENCY	NOTE	ODOMETER READING (NOTE 1)								REFER TO PAGE	
			X 1,000 mi	0.6	4	8	12	16	20	24		
			X 1,000 km	1.0	6.4	12.8	19.2	25.6	32.0	38.4		
EMISSION RELATED ITEMS	* FUEL LINE				I		I					3-5
	* THROTTLE OPERATION				I		I					3-5
	* AIR CLEANER	NOTE 2				R				R		3-6
	* SPARK PLUG				I	R	I	R	I	R		3-8
	* VALVE CLEARANCE							I				3-12
	ENGINE OIL			R		R		R		R		3-17
	ENGINE OIL FILTER			R		R		R		R		3-17
	* ENGINE IDLE SPEED			I	I	I	I	I	I	I		3-20
	RADIATOR COOLANT	NOTE 3				I		I		R		3-20
	* COOLING SYSTEM					I		I		I		3-20
	* SECONDARY AIR SUPPLY SYSTEM					I		I		I		3-21
	* EVAPORATIVE EMISSION CONTROL SYSTEM	NOTE 4						I		I		3-22
NON-EMISSION RELATED ITEMS	DRIVE CHAIN			EVERY 500 mi (800 km) I, L								3-22
	BRAKE FLUID	NOTE 3			I	I	R	I	I	R		3-26
	BRAKE PADS WEAR				I	I	I	I	I	I		3-27
	BRAKE SYSTEM			I		I		I		I		3-27
	* BRAKE LIGHT SWITCH					I		I		I		3-29
	* HEADLIGHT AIM					I		I		I		3-29
	CLUTCH SYSTEM					I		I		I		3-30
	CLUTCH FLUID	NOTE 3			I	I	R	I	I	R		3-30
	SIDE STAND					I		I		I		3-31
	* SUSPENSION					I		I		I		3-31
	* NUTS, BOLTS, FASTENERS			I		I		I		I		3-32
	** WHEELS/TIRES					I		I		I		3-33
** STEERING HEAD BEARINGS			I		I		I		I		3-33	

* Should be serviced by an authorized HONDA dealer, unless the owner has proper tools and service data and is mechanically qualified.

** In the interest of safety, we recommend these items be serviced only by an authorized HONDA dealer.

- NOTES:
- At higher odometer reading, repeat at the frequency interval established here.
 - Service more frequently if the motorcycle is ridden in unusually wet or dusty areas.
 - Replace every 2 years, or at the indicated odometer interval, whichever comes first. Replacement requires mechanical skill.