

ITEM		SPECIFICATIONS	
Bulbs	Headlight	High beam	12V - 55W
		Low beam	12V - 55W
	Brake/tail light	'99:	12V - 21/5 W × 2
		After '99:	12V - 32/3CP × 2
	Front turn signal/running light		12V - 32/3CP × 2
	Rear turn signal light		12V - 32CP × 2
	License light		12V - 4CP
	Instrument light	'99:	12V - 1.7 W × 4
		After '99:	12V - 1.4 W × 2
	Turn signal indicator	'99:	12V - 3W × 2
		After '99:	LED
	High beam indicator	'99:	12V 3W
		After '99:	LED
	Neutral indicator	'99:	12V - 3W
		After '99:	LED
Oil pressure indicator	'99:	12V - 3W	
	After '99:	LED	
PGM-FI warning indicator	'99:	12V - 3W	
	After '99:	LED	
Fuse	Main fuse	30A	
	PGM-FI fuse	30A	
	Sub fuse	20A × 2, 10A × 5	
Tachometer peak voltage		10.5 V minimum	
Thermo sensor resistance	80 °C	47.5 - 56.8 kΩ	
	120 °C	14.9 - 17.3 kΩ	
Fuel level sensor resistance	Full	4 - 10 Ω	
	Empty	81 - 91 Ω	
Fan motor switch	Start to close (ON)	98 - 102 °C (208 - 216 °F)	
	Stop to open	93 - 97 °C (199 - 207 °F)	

TORQUE VALUES

Side stand mounting bolt	10 N·m (1.0 kgf·m , 7 lbf·ft)	
Side stand lock nut	29 N·m (3.0 kgf·m , 22 lbf·ft)	
Side stand switch mounting bolt	10 N·m (1.0 kgf·m , 7 lbf·ft)	ALOC bolt.
Side stand bracket bolt	54 N·m (5.5 kgf·m , 40 lbf·ft)	ALOC bolt.
Ignition switch mounting bolt	25 N·m (2.5 kgf·m , 18 lbf·ft)	
Coolant temperature sensor	10 N·m (1.0 kgf·m , 7 lbf·ft)	Apply sealant to the threads.
Neutral switch	12 N·m (1.2 kgf·m , 9 lbf·ft)	
Oil pressure switch	12 N·m (1.2 kgf·m , 9 lbf·ft)	Apply sealant to the threads.
Oil pressure switch terminal screw	2 N·m (0.2 kgf·m , 1.4 lbf·ft)	